











TECHINCAL SPECIFICATIONS

- 1) SHOREBLOCK * PM UNITS ARE MANUFACTURED IN ACCORDANCE WITH ASTM C90 AND C140 AND THE FOLLOWING CRITERIA:
 - A) CONCRETE UNIT WEIGHT 130 -150 LBS/CF
 - B) MINIMUM COMPRESSIVE STRENGTH 4,000 PSI.
 - C) MAXIMUM ABSORPTION 5 %
 - D) DIMENSIONAL TOLERANCE ± 1/8"
- 2) GALVANIZED OR POLYESTER CABLING

FEMALE BLOCK ARE USED ON THE OUTSIDE OF THE MATS TO ALLOW CRIMPING.

UNIT	WEIGHT LBS.	COVERAGE (lbs/sq.ft)	OPEN ARE
PM-900 OC	127 - 146	73 - 82	20%

ASSEMBLY SPECIFICATIONS

- 1) SHOREBLOCK? PM UNITS ARE SHOP ASSEMBLED IN A CABLED MATTERESS AS SHOWN ABOVE.
- 2) SHOREBLOCK? PM MATS ARE PLACED BY THE CONTRACTOR IN THE FIELD ON PREPARED SLOPES PER THE CONTRACT DRAWINGS.

SHORETEC® L.L.C

510 O'NEAL LANE Baton Rouge, Louisiana 70819 (225) 408-1444 - Phone (225) 408-1445 - Fax www.shoretec.com

SHORETEC® PM PIPELINE MAT SE PM-900 OPEN CELL

	No.	Date	Revision	Ву	DIS TH
ERIES					KN Fil
					FII RE
					_
					TH DC
					DC IN

DISCLAIMER

DISCLAMENT
THE INFORMATION CONTAINED HEREIN HAS BEEN COMPLIED BY SHORETEC® LLC AND TO THE BEST OF OUR
KNOWLEDGE, ACCURATELY REPRESENTS THE SHOREBLOCK® PRODUCT USE IN THE APPLICATIONS WHICH ARE ILLUSTRATED.
FINAL DETERMINATION OF THE SUITABILITY FOR THE USE CONTEMPLATED AND ITS MANNER OF USE ARE THE SOLE
RESPONSIBILITY OF THE USER. STRUCTURAL DESIGN AND ANALYSIS SHALL BE PERFORMED BY A QUALIFIED ENGINEER.

THIS DRAWING IS BEING FURNISHED FOR THIS SPECIFIC PROJECT ONLY. ANY PARTY ACCEPTING THIS DOCUMENT DOES SO IN CONFIDENCE AND AGREES THAT IT SHALL NOT BE DUPLICATED IN WHOLE OR IN PART, NOR DISCLOSED TO OTHERS WITHOUT THE CONSENT OF SHORETEC® LLC.